SERIES 7000/8000 3-PIECE FULL PORT BALL VALVE PART NUMBERING

PART NUMBER - VALVE SELECTION												
Series	Size	-	Base Code	Body	Ball/ Stem	Seats	Seals	-	Service Mod	Ball Mod	-	Special Features
14	0200	-	11001	S	S	R	R	-	N	Ν		
1	2	-	3	4	5	6	7	-	8	9		-10
	Example: 140	0200-11001	SSRR-NN = 2" 7000 with	n SW (Socketv	veld Ends), S	tainless Stee	el Body, Stai	nless Steel	Ball and Stem, RF	PTFE Seats,	RPTFE Se	als
1	Series	14	3 Piece Valves	7000 Model 8000 Model	W	<u>ebsite Lir</u>	n <u>k</u> Bro	<u>ochure</u>	DM7000 DM8000	<u>Website</u>	Link	Brochure
		0025	1/4"			0100	1"			0250	2-1/2"	
2	Size*	0038 0050	3/8" 1/2"			0125 0150	1-1/4" 1-1/2"			0300 0400	3" 4"	
		0075	3/4"			0200	2"			0600	6"	
-	-											
		11000	Model 7000/8000 v	v/ NPT Ends				110M0	Model DM70	000/DM800	0 w/ NPT I	Ends
		11001	Model 7000/8000 v	v/ SW Ends				110M1	Model DM70	000/DM800	0 w/ SW E	nds
	Base Code	11002	Model 7000/8000 w/ BW Ends					110M2	Model DM7000/DM8000 w/ BW Ends (Sch40)			
3	(Model)	11023	Model 7000/8000 w/ Extended SW Ends					110M3	Model DM7000/DM8000 w/ Ext SW Ends			
		11024	Model 7000/8000 w/ Extended BW Ends (Sch40)					110M4	Model DM7000/DM8000 w/ Ext BW Ends (Sch40)			
		11013	Model 7000/8000 w/ NPT x SW Ends					110M7	Model DM7000/DM8000 w/ ANSI 150 Flanged Ends			
		11017	Model 7000/8000 w/ ANSI 150 Flanged Ends					11F00	Model 7000 w/ NPT Ends (NSF 61)			
4	Body S 316 Stainless Steel (7000 & DM7000)						A	Alloy 20				
		С	WCB Carbon Steel	l (8000 and D	M8000)							
5	Ball & Stem	S 316 Stainless Steel Ball with 316 Stainless Steel Stem						Alloy 20 Ball and Alloy 20 Stem				
		5	5 To Stainless Stee		o Stainless a	Sleer Slem		A	Alloy 20 Ball	and Alloy A	20 Stem	
		R	RPTFE					U	UHMWPE			
6	Seats	J K	TFM 1600 Tek-Fil					T F	PTFE RPTFE (NSI	F 61 Regist	tered)	
										o i i togioi		
7	Seals	R	RPTFE					U	UHMWPE			
		J F	TFM 1600 RPTFE (NSF 61 R	eaistered)				Т	PTFE			
-				-3,								
		N1	Neza					~	0	1		
8	Service N None Modification C General Cleaning						X F	Oxygen Cleaning NSF 61 Certification and Tagging				
											00 0	
9	Ball Modification	N H	None Vented Ball									
			Control Dun									
-	-											
10	Special	0001 Cavity Fillers 0031 Polished 10-15				d 10-15 Ra		0055	Special T	rust Wash	er Material Consult Factory	
	Features	0009	Polished to 30-35 F	Ra Polished	0210		d 8-12 Ra		????			,
	(Optional)	0032	to 20-25 Ra									

5 Bray

NOTES:

7000 & 8000 Model Valves come standard with a Lockable Lever. DM7000 & DM8000 come bare stem.

*Direct Mount Valves (DM7000/DM8000) are only Available in 1/2" - 2" Size Range. See Price Pages for sizes and End Connections

Special End Connections like other Schedule BW end caps are available on request - Consult Factory

Not all End Connections are available in all sizes - See price pages

General Cleaning per Bray WI-125 (solvent method) & Bagged meets ASME BPE-2002A Stainless Steel Welded Ends are made of 316L - ASTM A351 Gr CF3M Special Materials of Construction are available on request.