

PART NUMBER - VALVE SELECTION

Series	Size	-	Base Code	Body	Ball/ Stem	Seats	Seals	-	Service Mod	Ball Mod	-	Special Features
15	0600	-	11000	S	S	K	R	-	N	A	-	
1	2	-	3	4	5	6	7	-	8	9	-	10

Example: 150600-11000SSKR-NA = 6" F15, Full Port, ANSI 150 RF Flanged Ends, Stainless Steel Body, Ball and Stem, Tek-Fil Seats, RPTFE Seals, 30° V-Port

1	Series	15	Flanged Series - Floating Ball Valves V Control Brochure Technical Bulletin TB1006- V Control Selection									
2	Size	0050	1/2"	(Full Port Only)	0200	2"	(Full Port Only)	0600	6"			
		0075	3/4"	(Full Port Only)	0250	2-1/2"	(Full Port Only)	0800	8"			
		0100	1"	0300	3"	1000	10"					
		0150	1-1/2"	0400	4"	1200	12"					
-	-											
3	Base Code (Model)	11000	F15 - Full Port - ANSI 150 RF Flanged Ends				11001	RF15 - Standard Port - ANSI 150 RF Flanged Ends				
		11002	F30 - Full Port - ANSI 300 RF Flanged Ends F15/F30 Website				11021	RF30 - Standard Port - ANSI 300 RF Flanged Ends RF15/RF30 Website				
4	Body	S	316 Stainless Steel				?	Special Materials (Consult Factory)				
		C	WCB Carbon Steel									
5	Ball & Stem	S	316 Stainless Steel Ball with 316 Stainless Steel Stem				D	316 Stainless Steel Ball with 17-4 SS Stem				
6	Seats	K	Tek-Fil				U	UHMWPE				
							P	PEEK*				
7	Seals	G	Graphite				U	UHMWPE				
		R	RPTFE				K	Tek-Fil				
		J	TFM 1600				T	PTFE				
-	-											
8	Service Modification	N	None				X	Oxygen Cleaning				
		C	General Cleaning				M	NACE MRO 175 2003 (Upgraded Bolting - F15/F30)				
9	Ball Modification	J	15° V-Port		F	90° V-Port		G	75° V-Port			
		A	30° V-Port		E	120° V-Port		C	Custom Cut (Requires -???? Special Feature)			
		B	60° V-Port		P	45° V-Port		D	Slotted Cut (Requires -???? Special Feature)			
-	-											
10	Special Features (Optional)	0001	Cavity Fillers		0009	Polished to 30-35 Ra		0055	Special Trust Washer Material			
		0005	Slotted = 1/16"		0032	Polished to 20-25 Ra		0088	Upstream Vented w/ V-Port			
		0006	Slotted = 1/32"		0031	Polished 10-15 Ra		????	Custom Cut - ##° to Full or ##° at ###%			
		0117	Slotted = 1/8"		0210	Polished 8-12 Ra		????	Consult Factory			

NOTES:

15 Series Valves come standard with a Lockable Lever. Recommended to add a Gear Operator for 6" Full Port and up.

Not all sizes are available in Standard Port (RF15/RF30) Models - See price pages

*17-4 Stem is Required when using PEEK seats

Stainless Steel Spiral Wound Graphite Body Seal is standard on F15/F30 unless otherwise requested.

Flat Face Flanged Ends or RTJ Flanged Ends are available on request.

General Cleaning per Bray WI-125 (solvent method) & Bagged meets ASME BPE-2002A

Cavity Fillers only Available in F15 and F30 Models

Special Materials of Construction are available on request.

Special V Port Angles are available on request.

