

OVERVIEW

The 2-Cx lined butterfly valve features a state-of-the-art design which provides excellent shutoff protection and high flow rates with an exceptionally long service life. It has been specifically engineered to meet the stringent demands of the Chemical Industry.

MEDIA

- > Chlorine
- > Chlorine Dioxide
- > Hydriodic Acid
- > Hydrobromic Acid
- > Hydrochloric Acid
- > Hydrofluoric Acid
- > Hydrofluorsilicic Acid
- > Hydrogen Chloride
- > Hydrogen Cyanide
- > Nitric Acid
- > Sodium Chlorate
- > Sodium Chlorite
- > Sodium Hypochlorite
- > Sulfuric Acid



SPECIFICATIONS

Size Range¹	DN 50 to 600	
Temperature Range	-10°C to 200°C	
Maximum Operating Pressure (Bidirectional)	DN 50 to 600:	10 bar
Maximum Operating Pressure (Dead End Service²)	DN 50 to 300:	5 bar
	DN 350 to 600:	3 bar
Body Style³	Series 22-Cx:	Two-piece wafer
	Series 23-Cx:	Two-piece lug
Tightness Test	EN 12266-1 Rate A	
Velocity Limits (On-Off Service)	Fluids:	9 m/s
	Gases:	54 m/s

NOTES

- 1 Other sizes on request.
2 Lug body only.
3 Series 23-Cx DN 600 body style is double flange only.

DESIGN STANDARDS

Valve Design	EN 12569 EN 593 NE 167
Material Standard	EN 16668 AD2000 W0
Food Contact	EC 1935
Marking	EN 19 DIN EN IEC 61406 DIN 91406
Top Flange	ISO 5211
Flange Drilling	EN 1092-1 PN 10
Face-to-Face	EN 558 Series 20
Testing Standard	EN 12266-1 & 2
AutoID/ID Link	DIN 91406/IEC 61406

MATERIAL OPTIONS¹

Body	Ductile Iron, Low Temperature (EN 5.3103)
Disc (PTFE-lined)	Stainless Steel (EN 1.4408)
Stem	Stainless Steel (EN 1.4542)
Seat	PTFE
Seat Energizer	FKM
Body Fasteners	A4-70

NOTES

- 1 Other materials are available on request.

CERTIFICATIONS & APPROVALS

Certifications	CE: PED 2014/68/EU
	SIL 3 capable
Fugitive Emissions	ISO 15848-1
	TA-Luft 2021
Approvals	ATEX 2014/34/EU

FEATURES

- 1 ANTI-STATIC:** Electrostatic discharge through anti-static design (grounding device and top flange drilling).
- 2 STEM DESIGN:** The high-strength stem design includes blowout-proof functionality for safe operation and exceptional service life.
- 3 STEM BUSHING:** Non-corrosive, heavy duty acetal bushing absorbs actuator side thrust.
- 4 DIGITAL TAG:** Each valve is uniquely and easily identifiable by simply scanning the QR Code on the product identification tag in accordance to IEC 61406.
- 5 BEARINGS:** PTFE impregnated steel bearings precisely align the upper and lower stem.
- 6 STEM SEAL SYSTEM:** The live-loaded, self-adjusting packing design features a primary and secondary sealing principle to comply with the most stringent fugitive emission requirements.
- 7 SEAT:** The unique virgin-PTFE (minimum 3 mm thick) seat features a geometry that lowers seating and unseating torque while reducing wear on the contacting parts.
- 8 SEAT ENERGIZER:** A resilient seat energizer extends completely around the seat, including the disc hub providing uniform force sufficient for zero-leakage.
- 9 DISC:** The disc is encapsulated in virgin-PTFE (minimum 3 mm thick) for superior sealing against the most aggressive media.

